

VIRPI-M

~30° medium beam


TECHNICAL SPECIFICATIONS:

Dimensions	74.9 mm
Height	9.5 mm
Fastening	glue, pin
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	12.2 kg
Quantity in Box	360 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
VIRPI-M	Lens array	PMMA	clear





PHOTOMETRIC DATA (MEASURED):





LED ML-E
 FWHM 29.0°
 Efficiency 91 %
 Peak intensity 2.500 cd/lm
 Required components:





LED XB-D
 FWHM 28.0°
 Efficiency 92 %
 Peak intensity 2.830 cd/lm
 Required components:



LED XH-B/G
 FWHM 30.0°
 Efficiency 90 %
 Peak intensity 2.400 cd/lm
 Required components:





LED XP-E2
 FWHM 28.0°
 Efficiency 91 %
 Peak intensity 3.000 cd/lm
 Required components:




PHOTOMETRIC DATA (MEASURED):





LED XP-G
 FWHM 29.0°
 Efficiency 92 %
 Peak intensity 2.530 cd/lm
 Required components:




LED XP-G2
 FWHM 29.0°
 Efficiency 91 %
 Peak intensity 2.700 cd/lm
 Required components:



LED XT-E
 FWHM 29.0°
 Efficiency 91 %
 Peak intensity 2.620 cd/lm
 Required components:





LED LG 3030
 FWHM 28.0°
 Efficiency 91 %
 Peak intensity 2.800 cd/lm
 Required components:





PHOTOMETRIC DATA (MEASURED):





LED LUXEON Rebel ES
FWHM 28.0°
Efficiency 91 %
Peak intensity 2.620 cd/lm
Required components:





LED NF2x757A
FWHM 28.0°
Efficiency 92 %
Peak intensity 2.900 cd/lm
Required components:



LED NVSxx19A
FWHM 29.0°
Efficiency 90 %
Peak intensity 2.580 cd/lm
Required components:




LED Duris S5 (Single chip)
FWHM 28.0°
Efficiency 92 %
Peak intensity 3.100 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):



OSRAM
Opto Semiconductors

LED OSCONIQ P 2226
FWHM 29.0°
Efficiency 90 %
Peak intensity 2.600 cd/lm
Required components:




OSRAM
Opto Semiconductors

LED Oslon Square EC
FWHM 28.0°
Efficiency 91 %
Peak intensity 2.820 cd/lm
Required components:



SAMSUNG


LED LM231 A/B
FWHM 28.0°
Efficiency 92 %
Peak intensity 3.100 cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):


LUMILEDS

LED LUXEON C
FWHM 23.0°
Efficiency 86 %
Peak intensity 3.700 cd/lm
Required components:



LUMILEDS

LED LUXEON CZ
FWHM 20.0°
Efficiency 94 %
Peak intensity 4.800 cd/lm
Required components:



LUMILEDS

LED LUXEON SunPlus 20 Line
FWHM 27.0°
Efficiency 88 %
Peak intensity 3.400 cd/lm
Required components:


LUMILEDS

LED LUXEON SunPlus 35 Line
FWHM 26.0°
Efficiency 93 %
Peak intensity 3.600 cd/lm
Required components:


PHOTOMETRIC DATA (SIMULATED):




LED LUXEON T
 FWHM 26.0°
 Efficiency 91 %
 Peak intensity 3.350 cd/lm
 Required components:




LED LUXEON TX
 FWHM 27.0°
 Efficiency 92 %
 Peak intensity 3.250 cd/lm
 Required components:



LED NVSxx19B/NVSxx19C
 FWHM 27.0°
 Efficiency 94 %
 Peak intensity 3.190 cd/lm
 Required components:




LED Oslon Square Gen3
 FWHM 26.0°
 Efficiency 93 %
 Peak intensity 3.400 cd/lm
 Required components:



PHOTOMETRIC DATA (SIMULATED):


SAMSUNG

LED LH351B
FWHM 27.0°
Efficiency 94 %
Peak intensity 2.975 cd/lm
Required components:




SAMSUNG

LED LH351C
FWHM 28.0°
Efficiency 94 %
Peak intensity 2.799 cd/lm
Required components:



SEOUL SEMICONDUCTOR

LED Z8Y22
FWHM 26.4°
Efficiency 94 %
Peak intensity 2.900 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)