



Part Number: 5300FH

Security & Sound, 2 Conductor 18 AWG, TC, Shielded, Riser

# **Product Description**

Security & Commercial Audio Cable, 2 Conductor 18 AWG stranded (7x26) tinned copper conductors with polyolefin insulation, Beldfoil® shield, Riser, PVC jacket with ripcord.

## **Technical Specifications**

### **Product Overview**

Environmental Space:	Indoor - Riser
Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems

### **Physical Characteristics (Overall)**

### Conductor

AWG	Stranding	Material	No. of Cond	ductors
18	7x26	TC - Tinned Copper	2	
Condu	ctor Count:			2
Condu	ctor Size:			18 AW

## Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PP - Polypropylene	0.062 in	0.008 in

# **Color Chart**

Number	Color
1	Black
2	Red

### **Outer Shield Material**

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	24

### **Outer Jacket Material**

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.017 in

# **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
6.5 Ohm/1000ft	16.25 Ohm/1000ft

# Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
53 pF/ft	95.5 pF/ft
Shielding:	Foil(s) or Copper Tape(s)

### Inductance



### Current

# Max. Recommended Current [A] Per conductor @ 25°C: 5 A

# Voltage



# **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

# **Mechanical Characteristics**

Bulk Cable Weight:	18 lbs/1000ft
Max Recommended Pulling Tension:	57.5 lbs
Min Bend Radius/Minor Axis:	1.75 in

# **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes

# Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

# Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1666 Vertical Shaft
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6300FH

### **Part Number**

# Variants

Item #	Color
5300FH 0101000	Black
5300FH 0081000	Gray
5300FH 008500	Gray
5300FH 008U1000	Gray
5300FH 008U500	Gray

#### © 2018 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.